

**CARBONX CARBO 5.5****VISOKO KVALITETNA ZAŠČITNA ODEJA ZA VARJENJE****Tehnični list**

<b>CARBONX oksid polyakrilon. karbon /aramid</b>			
struktura		twill tkanina laminiran filc	
barva		črna	
teža	gr/m2	980	
standardi		EN ISO 11611:2008	
		EN ISO 11612:2010	A1,A2,B4,C2,D3,E3,F1
		EN ISO 1149:2004	
		EN ISO 14116:2008	3/S/60
		EN ISO 13937-2:2001	Pass
		EN ISO 15025:2000	Pass A1
		ISO 9151:1995 80kW/m2	B4
		ISO 6942:2002 B 20kW/m2	C2 Class 2
		EN ISO 9150	Class 1 >15 drops Class 2 > 25 drops
		EN ISO 1149-2	Pass
		ISO 1294-2	Pass
<b>CARBONX oksid polyakrilon. karbon</b>			
teža	gr/m2	200	
debelina	mm	5	
pretržna sila	N/5cm	90	
prepustnost zraka	l/m2/s 200pa	1400	
sestava			
karbon	%	62	
dušik	%	21.5	
kisik	%	12	
el upornost	Ohms cm	$8 \times 10^8$	
test vnetljivosti kisik index		ISO 4589, ASTM 2863	
LOI index	%	40+	
velikost vlaken	micron	12.5	
kisik	%	12	
<b>SUKANEC</b>		aramid	
<b>ROBNI TRAK</b>		fiberglass 0.18	
<b>RINKE</b>		medenina/nikelj o12	

